

## Product Overview

It's a PC base IP Surveillance Central Monitor Station (CMS) that installed on your Server, which can be direct simultaneous record by bunch of the model and brands. It could intergraded with the Internet cameras up to 1~128 pcs together. This software is easy to install and use on windows platform. Simply GUI design for AP or Web, and which also supports the Central Management System (CMS2000), which allows the control of unlimited cameras up to 2500 pcs, which suitable for large enterprises scale. Finally. The device is built-in with powerful recoding feature inside. Users can select 3 compression format as M-JPEG/H.264/MPEG4. Otherwise, CMS also allows users to remote access and view live video streams at any where, any time by 3GPP support.



## CM1000

## Features

Model	CM1100 (Standard)	CM1101 (Advanced)	CM1001 (Advanced)
IP Cameras Support	32 / 64 CH	64 / 128 CH	64 / 128 CH
GUI	AP	AP	WEB (IE 7)
Data Base	Access	SQL	SQL
Account	Yes (Admin)	Yes (Admin /User/ Group)	Yes (Admin /User/ Group)
Alarm	No	Yes	Yes
Group	Yes	Yes	Yes
Full Screen Ready	No	Yes	Yes
Compression Format	Motion JPEG / MJPEG4 / H.264(*)		
E-MAP Support	Single	Multiple	Multiple
File format	. AVI		
Record Type	RTC, Schedule	RTC, Schedule, DI, Motion	RTC, Schedule, DI, Motion
File System Type	EXT3		
IP CAM Setup	Yes (Basic)	Yes	Yes
Playback	Yes(1ch)	Yes(1/4ch)	Yes(1/4ch)
PTZ	Yes (Basic)	Yes (preset/PT Speed...)	Yes (preset/PT Speed...)
Support Brands	Bundle (One)	Multiple	Multiple
CMS2000 Support	No	Yes	Yes
Languages GUI	English	English / Traditional Chinese (*)	

(\*)Feature Enhance

### Qualified Recording Application

- \* It's a powerful NVR supports Real-time live viewing, recording and playback on different channel at the same time
- \* Support Alarm signal form Central Management System (CMS2000)
- \* Advanced recording function: 4 different classes of RTC, MOTION, Schedule, and DI
- \* Build intelligent WATCHDOG technology

### SMB/ Enterprise Scale Surveillance

- \* It supports 1~128 channel M-JPEG /MPEG4/H.264 Simultaneous recording at the same time
- \* It supports up WEB or AP GUI
- \* Support all PTZ control through RS-485 and IR remote control operating for SMB /Enterprise surveillance purpose
- \* It supports for many 3rd-party IP camera brands and models

### Easy Installation and Operation

- \* It supports WEB or AP GUI to suitable for various operation purpose
- \* Easy HDD built-in formatting
- \* Easy IP cameras , user ,and group setting

### Package Content

- \* CD(with electric User's Manual, Installation Guide)

### PC Minimum Requirement

- \* Operation System: Microsoft Windows 2000 / XPP/ 2003 server (R1)/ Vista
- \* CPU: Intel Core 2 Duo 2.4 GHz or above ( 128CH recommends Quad 2 Duo )
- \* Memory: Memory: 2G or above ( 4G recommends on 128ch )
- \* VGA Card: Individual AGP(4X) VGA card recommend
- \* Microsoft DirectX 9.0c. or above version inside recommend