

Features

- 1/3" Sony Super HAD CCD , 550 TV Lines
- 4 multi-profile for MPEG4 VGA/ MPEG4 QVGA/ MPEG QQVGA/ MJPEG (selectable) modes; 30 fps for all video resolutions
- Supports TCP/IP networking, SMTP e-mail, FTP, HTTP and other Internet related protocols
- 1 sensor in, 1 alarm output. When DO is triggered send video file to email, FTP, audio alert
- 3GPP mobile phone surveillance
- Two-way audio for remote conversation and voice warning



CCD BOX IP Camera (PoE)

YCS6021

Specification

Ethernet	10/100MB Tx		
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, UPnP™, RTSP, PPPoE, 3GPP		
Video			
Image Sensor	1/3" Sony Super HAD CCD	Camera DSP	SONY HQ1
Image Pixel	NTSC:811(H) × 508(V) / PAL:795(H) × 596(V)		
Sensor Resolution	550 TV Lines		
Sensitivity	0.5 Lux@F2.0		
Lens Type	CS mount lens selectable		
Video Profile	4 video profiles simultaneously 1) MPEG4 VGA/ 2)MPEG4 QVGA/ 3)MPEG4 QQVGA 4) MJPEG VGA/ QVGA/ QQVGA (selectable)		
Video Resolution	640*480/ 320*240/ 160*120		
Image Frame Rate	Max. 30 fps(N), 25fps (P) for all resolutions		
Audio			
Audio Support	AMR/G.726		
2-way Audio	Simplex / Duplex 2-way audio		
3GPP Cell Phone	3GPP mobile surveillance. Audio+video		
Power over Ethernet	X		
System			
Browser	IE 6.0 or latter		
Easy DDNS Service	DIPS®		
UPnP Level	UPnP Discover & Auto port forwarding		
I/O port			
DI/DO	DI:1/DO:1		
Audio Input	Internal MIC or Phone jack to external MIC		
Audio Output	Line out		
Video Output	Composite 1.0 Vp-p at 75 ohm		
Iris Control	DC drive		
Motion Detection	4 zones		
Pre-recording	V		
Send E-mail / FTP/ Voice Alert	V		
Bundle	Bundle 16ch Software		

Software

Supported OS	Windows 2000/ XP/ Vista
Application Software	View channel:16 CHs Record Playback Motion detect Backup/ Restore to/ from Configuration file
IP Wizwrd	Auto search IP Address of Camera in LAN

What's included

Network Camera x 1 Antenna x 1 (Wireless model only) Mounting Kit x 1 Power Adapter (12V, 1A) x 1 Quick Installation Guide x 1 CD-ROM (Softwares & Doc) x 1
