

Features

- Multi-profile video, MPEG4 & JPEG simultaneously dual encoders, multi-resolution
- 3GPP mobile phone support
- RS485 for speed dome control
- External alarm Input/ Output, build in motion detection
- Power over Ethernet option



MPEG 4 Video Server (LAN)

YVS2100

Specification

Camera IYVS2100	
Video Input	1 channel, BNC connector
Audio Input	1 channel, RCA audio in
Digital I/O	DI *1, DO *1
RS485	For speed dome control
Power Input	12V DC, 1.5A adaptor
System/Network	
Video Encoder	MPEG4-SP and JPEG simultaneously
Video Profile	4 profiles simultaneously - MPEG4 VGA - MPEG4 QVGA - MPEG4 QQVGA - JPEG VGA/ QVGA/ QQVGA
Video Resolution	Up to 30fps @ 640x480 Up to 30fps @ 320x240 Up to 30fps @ 160x120
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, NTP, RTP, RTSP, DNS, DHCP, UPnP, DDNS, PPPoE
Ethernet	100Base-TX/ 10Base-T(RJ-45x1)
Audio	2-way audio application G.726 GSM AMR
Motion Detection	4 areas. Independent sensitivity
Digital zoom	Adjustable digital zoom area No limit zoom ratio
Mobile Surveillance	3GPP protocol, Video and audio
Motion detection	4 areas. Independent sensitivity
Browser	Microsoft® Internet Explorer 6.0 or later
Security	2 Levels, Administrator or user
Ethernet	10/100M auto negotiation
Temperature	Operating : 0 to 50 °C
Bundle	Bundle 16ch Software

Software

Supported OS	Windows 2000/ XP/ Vista
Application Software	View channel:16 CHs Record Playback Motion detect Backup/ Restore to/ from Configuration file
IP Wizrd	Auto search IP Address of Camera in LAN

What's included

Network Camera x 1
Antenna x 1 (Wireless model only)
Power Adapter (12V, 1.5A) x 1
Quick Installation Guide x 1
CD-ROM (Softwares & Doc) x 1