

Features

- Multi-profile video, MPEG4 & JPEG simultaneously dual encoders, multi-resolution
- 3GPP mobile phone support
- RS485 for speed dome control
- External alarm Input/ Output, build in motion detection
- Power over Ethernet option



MPEG 4 Video Server (PoE)

YVS2120

Specification

| | |
|---------------------|--|
| Camera IYVS2120 | |
| Video Input | 1 channel, BNC connector |
| Audio Input | 1 channel, RCA audio in |
| Digital I/O | DI *1, DO *1 |
| RS485 | For speed dome control |
| Power Input | 12V DC, 1.5A adaptor |
| System/Network | |
| Video Encoder | MPEG4-SP and JPEG simultaneously |
| Video Profile | 4 profiles simultaneously - MPEG4 VGA - MPEG4 QVGA - MPEG4 QQVGA - JPEG VGA/ QVGA/ QQVGA |
| Video Resolution | Up to 30fps @ 640x480 Up to 30fps @ 320x240 Up to 30fps @ 160x120 |
| Networking Protocol | TCP/IP, HTTP, SMTP, FTP, NTP, RTP, RTSP, DNS, DHCP, UPnP, DDNS, PPPoE |
| Ethernet | 100Base-TX/ 10Base-T(RJ-45x1) |
| Audio | 2-way audio application G.726 GSM AMR |
| Motion Detection | 4 areas. Independent sensitivity |
| Digital zoom | Adjustable digital zoom area No limit zoom ratio |
| Mobile Surveillance | 3GPP protocol, Video and audio |
| Motion detection | 4 areas. Independent sensitivity |
| Browser | Microsoft® Internet Explorer 6.0 or later |
| Security | 2 Levels, Administrator or user |
| Ethernet | 10/100M auto negotiation |
| Temperature | Operating : 0 to 50 °C |
| Bundle | Bundle 16ch Software |

Software

| | |
|----------------------|---|
| Supported OS | Windows 2000/ XP/ Vista |
| Application Software | View channel:16 CHs Record Playback Motion detect Backup/ Restore to/ from Configuration file |
| IP Wizwrd | Auto search IP Address of Camera in LAN |

What's included

Network Camera x 1
Antenna x 1 (Wireless model only)
Power Adapter (12V, 1.5A) x 1
Quick Installation Guide x 1
CD-ROM (Softwares & Doc) x 1